

THE NEXT GENERATION



Certified 650kg CS-23

600kg S-LSA 600kg UL

flightdesign.com



Designed for your Mission	
Our Mission	
Advanced Aerodynamics	4
Land with Confidence	4
F2 Safety Cabin	4
Vision Zero	2
Get comfortable	
Firewall forward	
Standard equipment	6
Avionics and Cockpit choices	6
F2-LSA and 600KG UL panel	
F2 CS-23 Certified IFR panel	8
Graphic Designs	(
Technical information	1(

DESIGNED FOR YOUR

The F2 is the newest aircraft from Flight Design general aviation. One we think will define light aircraft safety, performance and comfort in an EASA CS-23 certified aircraft with an MTOW of 650 kg, or as an SLSA or Ultralight with 600 kg MTOW. The F2 brings a fresh look at high-wing light aircraft design with class leading safety features and an innovative Garmin G3X avionic suite.

The spacious extra-large cabin of the F2 has been designed for increased rigidity and incorporates a combination of dynamically tested passenger seats, panel-mounted AMSAFE ™ airbags and an Airframe Emergency Parachute System (AEPS) for your safety. The atmosphere inside the F2 is improved with many clever design features, the modern heating/fresh air system and comfortable leather covered, adjustable seating.

Our Mission

The worldwide flight training industry is looking for new ways to teach more pilots at lower cost, in greater safety and with lower environmental impact. Our mission has been to design the F2 for the demands of professional flight schools and flying clubs as well as private owners who want an easy to fly aircraft with efficiency and cruise performance for true cross-country adventures.

A modern aircraft should have all the features seeking to improve performance, situational awareness and reduce the pilot workload. The F2 includes:

so have the

 Garmin G3X avionics suite with synthetic vision,
ADS-B weather, traffic, engine monitoring and maps

- * Single lever throttle and brake system
- * AMSAFE airbags and inertial reel seat belts
- * Dynamically tested, adjustable seats
- * No touch fuel system with electric fuel gauges
- * DLE outer wing optimized for spin resistance
- * Drag reducing sculpted winglets
- * Wide composite main gear
- * Massive center tunnel for cabin rigidity
- * Low drag cowling with easy-to-latch system
- * Heat exchanger heating system
- * Electric trim and pre-selector flap system.
- * Cavernous rear cabin for luggage, bicycles or pets!

13

4 Advanced Aerodynamics

The F2 was designed specifically for EASA CS-23 certification and to meet the demanding ASTM F3180 low-speed flight characteristics of fixed-wing aircraft standard for spin resistance and stall warning. Sculpted winglets improve climb and cruising range. The smooth cantilever strutless wing reduces drag and allows maximum visibility from the cockpit.

The sculptured Carbon Fiber fuselage of the F2 is designed for extra-large volume in the cabin and to reduce drag while providing cleaner airflow to the tail. The large span stabilizer and separate elevator have been designed for optimum low speed control and better control feel. In total, the aerodynamic features have significantly improved the F2's stability, control and its overall ease of flying. While the top speed of the F2 is impressively high, the F2 flies with efficiency and low fuel consumption at all speeds. CFD based virtual wind tunnel design tools were used to complete the efficient and refined aerodynamic design.

F2 Safety Cabin

The F2 cockpit has been designed following principles used in the passenger cabins of modern automobiles. Loads are transferred through the passenger area to the crush-zones at the front end of the vehicle. The rigid cabin cell area remains intact while the energy is absorbed in the peripheral areas.

• The rigid engine mount transfers loads into the to the massive attachment to the center structural tunnel.

• The center of the cabin is stiffened with the structural tunnel from the nose gear area to beyond the luggage compartment.

• The area below the seats is reinforced with 'Pyramid structural members installed to the cabin floor, supporting the seats and further stiffening the floor.

• The outer skin is carbon fiber/honeycomb providing maximum stiffness and strength.

The suitability of this concept has been improved with data gathered from testing and in service now for 20 years. The service history shows that the cabin concept provides a maximum of occupant protection.

Land with Confidence

The wide-track composite main gear is extremely rugged while also being flexible, absorbing landing energy and protecting the structure. Urethane polymer shock absorbers in the nose gear give high dampening and help to smooth out hard landings.

The single throttle and brake lever system developed by Flight Design, simplifies power and brake management.



Vision zero

Vision Zero is our mission that zero occupants should face injuries even in a very serious incident. This can be achieved by a combination of passive and active safety systems.

Always pushing forward with new innovations to make flying more enjoyable and safer, Flight Design general aviation has now taken the F2 closer to the ideal of Vision Zero.

A spin resistant airplane with a car-like simplified fuel system, panel mounted airbags, better passenger restraints, and as back-up to those systems an integrated airframe emergency parachute system to protect you and your passenger.

Get Comfortable

The 1.3 m (51") Extra Large cabin width of the F2 has been designed to fit very tall and smaller people equally well. People with heights of 1.55 to 2.00 m (5' 1" to 6' 6") will sit more comfortably than ever. Ample storage space in the cockpit is provided by great access for bulky items stored aft of the cockpit. Four large cabin windows give the cockpit an open feeling and improve overall visibility.

Large gull–wing doors held up by gas struts make entering and taking your seat easy. Three–point latches and door seals keep you secure inside. The leather covered seats with Confor-foam padding offer comfort for long flights and easy adjustment in height and leg length.

Full dual controls and a centrally located single lever throttle/brake quadrant are features of this ergonomically arranged cockpit. Modern ventilation and heat exchanger heating allow you to fly comfortably in all 4 seasons. The F2 allows up to 40 kg (88 lbs.) of baggage to be safely stored in the giant storage space aft of the cabin area. If you are finding it hard to find an airplane that fits you, try the F2. We think you will be pleasantly surprised!

As a modern and advanced light aircraft, the F2 uses an engine that matches the efficient concept of the airframe, the Rotax [™] 912iS. The 912iS offers a high level of sophistication, redundancy and efficiency. With the Flight Design CFD designed split flow cooling systems keeps it cool even in the hottest climates. Oil and Coolant thermostats complete the temperature management and all systems are easily accessible under the easy to remove cowling.

The 912iS fuel injection system precisely controlled fuel-air mixture for dramatically lower C02 output, improved high altitude performance, more useful torque and improved fuel economy.

- 100-hp Rotax 912iS with fuel injection
- 1352 c.c. 10.5 : 1 compression ratio
- Gearbox: 2.43 : 1 reduction ratio
- Fuel types: Premium unleaded auto fuel or 100 LL Avgas



6 Standard Equipment

Avionics and Cockpit choices

BRS Airframe Parachute System AMSAFE panel mounted airbags Inertial-reel automotive-style seat belts Rotax 100 HP 912iS engine Stainless exhaust system Heat exchanger heat and panel ventilation Electric stabilizer trim and pre-selector flap control

Leather covered sport seats with Confor-foam padding

Gigantic storage area behind the cockpit Extra wide cabin doors with gas springs One-piece panoramic windshield Two wing tanks with 130 l (34 gallon) capacity Electric fuel level gauges Composite main landing gear with MATCO

hydraulic disc brakes, Steerable nose wheel, Wheel pants Fire Extinguisher and CO Detector A selection of optional graphic patterns Complete document package includes: Flight, Maintenance, Transition training and Parts Man-

Maintenance, Transiti ual Flight Design has been in the vanguard of the avionics revolution in light aircraft. With the F2 we offer an expanded range of avionics to suit your personal aviation mission. The F2 features some of the most advanced, yet easy to use avionics from Garmin including the G3X Touch screens for unmatched situational awareness, integration of the Rotax[®] engine management system, checklists and diagnostic functions.

(10)

(4)

The bright, high-definition G3X panel includes PFD, EMS and Map functions with a battery backup. With the Garmin GTX 345 transponder the F2 is compliant with the FAA's ADS-B 2020 "Out" requirements and has the complete ADS-B "in" features like Satellite based weather, traffic and real-time TFR notices. Depending on your needs, an additional navigation source can be provided by optional GNC 255 Nav/Com or a Garmin GTN 650. The Garmin GFC 500[™] Digital 2-axis autopilot with Level Button rounds out this well-balanced avionic suite.





-121.975***-128.075

AT 1200 PRESONE A

F2-LSA and 600kg UL panel

1	Garmin G3X GDU 460 Screen (10.6" landscape format)	
2	AMSAFE pilot and passenger Airbags	
3	GTR 225A com or 255 Com-Nav-com	
4	Optional Heated Pitot Probe switch	
5	Garmin G5 backup system	
6	Garmin GMC 507 Digital autopilot "mode controller panel"	
7	Artex 345 ELT 406 MHz with remote control	
8	GMA-342 stereo audio panel	
9	Garmin 345 ADS-B "in and out"	
10	Fresh air and heating vents	

....

(8)

3







ORACAL 951 series	070	Black
ORACAL 951 series	090	Silver grey
ORACAL 951 series	032	Light red



ORACAL 951 series	049	King Blue
ORACAL 951 series	090	Silver grey
ORACAL 951 series	052	Azure Blue

9



Wings:





SUMMARY OF PERFORMANCE SPECIFICATIONS

Maximum tested gross weight	650 kg (1433 lbs.)	
Total fuel capacity	130 l (34.3 gal)	
Approved Fuel – Premium Automotive unleaded	91Avgas -100 LL Avgas	
Maximum engine power	73.5 kW (100 hp) @ 5800 rpm	
* Range, full fuel, with 30 min reserve up to 1.000 NM = 1850km)		
* Maximum speed 136 kts (252 km/h) TAS at 5800 rpm at 7500 ft		
* Cruise speed 126 kts (233 km/h) TAS, at 75% power (5200 rpm) at 7500 ft		

* Projected and to be confirmed by flight testing

F2 Dimensions Main Dimensions:		
Wing span	9.872 m (32.3 ft)	

6.86 m (22.50 ft)

2.34 m (8.75 ft)

Length

Height

	Airfoils FD 144-44 inboard, FD 144-42 outboard
Wing area 11.1 sq. m (120 sq. ft)	
	Aspect ratio 8.7
	Mean Aerodynamic chord (MAC) 1.166 m (3.83 ft)



Horizontal Tail		ail	Cabin Width 1.29 m (50.5 inches)
Are	a	2.05 m ² (22.04 ft ²)	Maximum Takeoff Weight (MTOW): 650 kg (1433 lb.)
Spa	an	3.15 m (10.33 ft)	Basic Empty Weight 374 kg (824 lb.)



FLIGHT DESIGN general aviation GmbH Am Flugplatz 3 99820 Hörselberg-Hainich Germany phone: +49 36920 7530-10 email: info@flightdesign.com web: www.flightdesign.com



What is your mission?

Editorial responsibility & disclaimer

Information given in Flight Design brochures or in other printing matter may be subject to alteration without notice. Care has been taken to ensure that the contents of this publication are accurate but FLIGHT DESIGN general aviation GmbH and its subsidiaries do not accept responsibility for errors or for information which is found to be misleading. Suggestion for or descriptions of the end use or application of products or methods of working are for information only and FLIGHT DESIGN general aviation GmbH and its subsidiaries accept no lability in respect thereof. Before using products supplied or manufactured by FLIGHT DESIGN general aviation GmbH or its subsidiaries, the customer should satisfy themselves of their suitability.